



VITREOUS SILICA INSULATED
TYPE W-HG/HG (THERMOCOUPLE GRADE)

FIBERGLASS INSULATION

Individual conductors are insulated with a high temperature vitreous silica yarn. Conductors are laid parallel and covered with an overall high temperature vitreous silica yarn. A tracer is braided into the insulation for polarity and calibration identification. Not recommended for applications where insulation is subject to abrasion unless protected with a metallic overbraid.

PERFORMANCE FEATURES

Designed for continuous use to 1800° F (980° C),
intermittent to 2000° F (1095° C).
Asbestos replacement

APPLICATIONS

Ovens and Furnaces
Steel Industry
Furnace Temperature Surveys

CALIBRATION: ANSI Type J

ORDERING CODE		CONDUCTOR SIZE (AWG)	NOMINAL LOOP RESISTANCE (2)
STANDARD	SPECIAL (1)		
W-HG/HG-20F-J	W-HG/HG-20F-JJ	20 STRANDED	0.335
W-HG/HG-20-J	W-HG/HG-20-JJ	20 SOLID	0.367
W-HG/HG-18-J	W-HG/HG-18-JJ	18 SOLID	0.234
W-HG/HG-16-J	W-HG/HG-16-JJ	16 SOLID	0.145
W-HG/HG-14-J	W-HG/HG-14-JJ	14 SOLID	0.091

CALIBRATION: ANSI Type K

ORDERING CODE		CONDUCTOR SIZE (AWG)	NOMINAL LOOP RESISTANCE (2)
STANDARD	SPECIAL (1)		
W-HG/HG-20F-K	W-HG/HG-29F-KK	20 STRANDED	0.538
W-HG/HG-20-K	W-HG/HG-20-KK	20 SOLID	0.589
W-HG/HG-18-K	W-HG/HG-18-KK	18 SOLID	0.376
W-HG/HG-16-K	W-HG/HG-16-KK	16 SOLID	0.233
W-HG/HG-14-K	W-HG/HG-14-KK	14 SOLID	0.147

CALIBRATION: ANSI Type E

ORDERING CODE		CONDUCTOR SIZE (AWG)	NOMINAL LOOP RESISTANCE (2)
STANDARD	SPECIAL (1)		
W-HG/HG-20F-E	W-HG/HG-20F-EE	20 STRANDED	0.648
W-HG/HG-20-E	W-HG/HG-20-EE	20 SOLID	0.709
W-HG/HG-18-E	W-HG/HG-18-EE	18 SOLID	0.453
W-HG/HG-16-E	W-HG/HG-16-EE	16 SOLID	0.281
W-HG/HG-14-E	W-HG/HG-14-EE	14 SOLID	0.177

CALIBRATION: ANSI Type N

ORDERING CODE		CONDUCTOR SIZE (AWG)	NOMINAL LOOP RESISTANCE (2)
STANDARD	SPECIAL (1)		
W-HG/HG-20F-N	W-HG/HG-20F-NN	20 STRANDED	0.715
W-HG/HG-20-N	W-HG/HG-20-NN	20 SOLID	0.783
W-HG/HG-18-N	W-HG/HG-18-NN	18 SOLID	0.500
W-HG/HG-16-N	W-HG/HG-16-NN	16 SOLID	0.310
W-HG/HG-14-N	W-HG/HG-14-NN	14 SOLID	0.195

CALIBRATION	COLOR CODE (ANSI)			COLOR CODE (IEC)*		
	POSITIVE	NEGATIVE	OVERALL	POSITIVE	NEGATIVE	OVERALL
TYPE J	WHITE	RED	WHITE	BLACK	WHITE	WHITE
TYPE K	YELLOW	RED	WHITE	GREEN	WHITE	WHITE
TYPE E	PURPLE	RED	WHITE	PURPLE	WHITE	WHITE
TYPE N	ORANGE	RED	WHITE	PINK	WHITE	PINK

* Add (-IEC) to the end of the ordering code for IEC color coded insulation and jacketed wire.
Example: W-HG/HG-20-J-IEC

INITIAL CALIBRATION TOLERANCES Per ANSI MC96.1 and ASTM E230 (°F)				
TEMPERATURE RANGE	STANDARD		SPECIAL	
	CALIBRATION	TOLERANCE	CALIBRATION	TOLERANCE
32 to 1400°F	TYPE J	±4.0°F or ±.75%*	TYPE JJ	±2.0°F or ±.4%*
32 to 2300°F	TYPE K	±4.0°F or ±.75%*	TYPE KK	±2.0°F or ±.4%*
32 to 1600°F	TYPE E	±3.0°F or ±.50%*	TYPE EE	±1.8°F or ±.5%*
32 to 2300°F	TYPE N	±4.0°F or ±.75%*	TYPE NN	±2.0°F or ±.4%*

*Whichever is greater.

CONDUCTOR SIZE (AWG)	INSULATION THICKNESS	JACKET THICKNESS	NOMINAL DIMENSIONS	APPROX. SHIPPING WT. lbs/1000 Ft. (Kg)
20 STRANDED	.016	.016	.102/.172	14 lbs (6.4 Kg)
20 SOLID	.016	.016	.096/.160	13 lbs (5.9 Kg)
18 SOLID	.016	.016	.104/.176	18 lbs (8.2 Kg)
16 SOLID	.016	.016	.115/.198	25 lbs (11.3 Kg)
14 SOLID	.016	.016	.128/.224	34 lbs (15.4 Kg)

Notes:

- (1) Meets or exceeds Special Initial Calibration Tolerances per ANSI MC96.1-1982 and ASTM E230-1993.
- (2) Nominal resistance in OHMS per double feet at 68°F (20°C).



SECTION WIRE
VITREOUS SILICA
INSULATED WIRE

The information contained herein shall be considered the sole property of Thermo Electric Corporation. The recipient thereof agree not to disclose or reproduce said information to parties outside the recipients organization without the written permission of Thermo Electric Corporation.

Doc. No.: TE-CO010109-WIRE-100